



**SPECIFICATIONS**

Memory Size 1 Mbytes + 512K Flash  
 Serial Ports 8/16 RS-232C  
 Serial Line Speeds 50 bps to 57.6K bps  
 Serial Port interface RJ-45 DTE  
 Standard Protocols TCP/IP, ARP, ICMP, UDP  
 TIME, FINGER, BOOTP  
 TFTP, DNS, TELNET  
 RLOGIN, SLIP, CSLIP  
 PPP, RIP

**SERIAL PORTS**

Character Width 5 to 8 bits  
 Stop Bits 1, 2 bits  
 Parity None, Even, Odd, Mark, Spc  
 Data Speed 50 to 57600 bps + autobaud  
 Modem Control DTR, DSR, RTS, CTS, DCD  
 Flow Control XON/XOFF, RTS/CTS  
 Interface EIA RS-232C  
 Connector Female RJ-45

**PARALLEL PORT**

Interface Centronics  
 Connector Female DB-25

**NETWORK**

Interface Ethernet / IEEE 802.3  
 Connector AUI (10Base 5), BNC (10Base 2)

**RFC Compliance**

IP and Options RFCs 791, 1122  
 ARP RFCs 826  
 ICMP RFCs 792, 1122  
 SLIP, CSLIP RFCs 1055, 1144  
 PPP RFCs 1331, 1332  
 BOOTP, TFTP RFCs 783, 906  
 TCP and Options RFCs 793, 1122  
 UDP RFCs 768  
 DNS RFCs 920, 1034, 1035  
 SNMP MIB-II RFCs 1089, 1155-1158, 1213  
 TELNET RFCs 854-861, 1123  
 RLOGIN RFCs 951, 1084  
 TIME RFCs 868  
 FINGER RFCs 1196  
 RIP RFCs 1058, 1388

**PHYSICAL**

Front Panel Indicators Power, Network Activity, Serial Line I/O Activity  
 Dimension 2" high x 19" wide x 11.5" deep (RACK MOUNT)  
 Power 110-220 V AC, 50-60Hz  
 Operating Environment Temperature 0 - 50°C  
 Humidity 10% - 90% non-condensing

**APPROVALS**

UL, CSA, and FCC Class-A

Copyright © 1997 GLOBAL VIEW CO., LTD.

**GLOBAL VIEW CO., LTD.**



\* All specifications subject to change at the manufacturer's discretion  
 \* All products are trademarks or registered trademarks of their respective manufacturers