



SPECIFICATIONS

Memory Size 4 Mbytes DRAM + 512K Flash
can upgrade to 8 Mbytes DRAM

Serial Ports 16 RS-232C

Serial Line Speeds 110 bps to 115.2K bps

Serial Port interface RJ-45 DTE

Standard Protocols TCP/IP, ARP, ICMP, UDP
TIME, FINGER, BOOTP
TFTP, DNS, TELNET
RLOGIN, SLIP, CSLIP
PPP, RIP, RADIUS

SERIAL PORTS

Character Width 5 to 8 bits

Stop Bits 1, 2 bits

Parity None, Even, Odd

Data Speed 110 to 115200 bps + autobaud

Modem Control DTR, DSR, RTS, CTS, DCD

Flow Control XON/XOFF, RTS/CTS

Interface EIA RS-232C

Connector Female RJ-45

PARALLEL PORT

Interface Centronics

Connector Female DB-25

NETWORK

Interface Ethernet / IEEE 802.3

Connector AUI(10 Base 5), BNC(10 Base 2)
UTP(10 Base T)

RFC Compliance

IP and Options RFCs 791, 1122

ARP RFCs 826

ICMP RFCs 792, 1122

SLIP, CSLIP RFCs 1055, 1144

PPP RFCs 1331, 1332

BOOTP, TFTP RFCs 783, 906

TCP and Options RFCs 793, 1122

UDP RFCs 768

DNS RFCs 920, 1034, 1035

SNMP MIB-II RFCs 1089, 1155-1158, 1213

TELNET RFCs 854-861, 1123

RLOGIN RFCs 951, 1084

TIME RFCs 868

FINGER RFCs 1196

RIP RFCs 1058, 1388

RADIUS RFCs 2138, 2139

PHYSICAL

Front Panel Indicators Power, Network Activity,
Serial Line I/O Activity

Dimension 2" high * 19" wide * 11.5"
deep (RACK MOUNT)

Power 90-264 VAC, 47-63Hz

Operating Environment Temperature 0-50°C
Humidity 10% - 90%
non-condensing

OPTION APPROVALS LCD Control Panel
UL, FCC Class-A

Copyright 1998 GLOBAL VIEW CO., LTD.



GLOBAL VIEW CO., LTD.

* All specifications subject to change at the manufacturer's discretion.
* All products are trademarks or registered trademarks of their respective manufacturers.