


# APLOG301-I

## PCI Bus Two Port Card

Support **Monitored feature in**  
**RS232 to Ground Isolated**  
**RS232/RS422/RS485 Converter**



- ★Port A can set to target RS232/RS422/RS485
- ★Easy to convert your standard RS232 COM1 port to Ground isolated RS232/RS422/RS485 settable interface.
- ★Two serial ports can monitor your data stream in converter.
- ★Ground isolated to protect your hardware. Monitor feature to protect your software.
- ★Suitable for Windows 2000/XP/7/8 and Linux system.

## **APLOG301-I Specification :**

### **Serial Communication Controller :**

\*type : ASIX chip MCS9865.

### **Hardware compatibility :**

\*5V or 3.3V PCI bus slot.

### **Software compatibility :**

- \* Windows 2000/XP.
- \* Windows Vista.
- \* WIN7/8.
- \* Linux.
- \* Other operating system

### **Dimension :**

- \* APLOG301-I card: 100 \* 97 mm.
- \* APLOG301-I model with standard PCI bracket.

### **System I/O & IRQ mapping :**

- \*I/O mapping assigned by PCI BIOS.
- \*Memory mapping assigned by PCI BIOS.
- \*IRQ mapping assigned by PCI BIOS.

### **Port capability :**

- \*number of port : 2 ports per card.
- \*Interface : Port B is RS232 and port A is Ground Isolated RS232/RS422/RS485

Note: port A can set to RS232/RS422/RS485 by DIP switch. Converter function between port A and port B and monitored by two serial ports.

- \*Baud Rate : each port can be configured to 50--115200bps.
- \*Connector type: DB9 male connector.

### **Environment :**

- \*operating temperature : 0°C to 55°C
- \*operating humidity : 10% to 95% RH
- \*storage temperature : 0°C to 65°C
- \*storage humidity : 5% to 95% RH

## **Performance upgrade capability and relative products :**

- \*AP102-I : PCI card support two Ground Isolated RS232 ports.
- \*AP132-I : PCI card support two Ground Isolated RS422/RS485 ports.
- \*AP112-I : PCI card support two Ground Isolated RS232/422/485 port.
- \*AP301-I : PCI card support one RS232 and one Ground Isolated RS232/422/485 port.
- \*AP112 : PCI card support two RS232/RS422/RS485 ports.
- \*AP132 : PCI card support two RS422/RS485 ports.
- \*APCON301-I : PCI card support RS232 to Ground Isolated RS232/RS422/RS485 ports.

\*\*\*All names are the trademarks of their respective organization.



### **RAYON TECHNOLOGY CO., LTD.**

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: [rayon@ms1.hinet.net](mailto:rayon@ms1.hinet.net) or [info@rayontech.com.tw](mailto:info@rayontech.com.tw)

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com.tw>