Universal PCI Eight Port Card

Flexible 5V power supply only PCI card

RS232 & RS422 selectable



- Suitable for Windows NT
- Suitable for WIN95/98/Me
- Suitable for WIN2000/XP
- Suitable for WIN2003/Vista
- Suitable for DOS Power User
- **Suitable for Linux System**
- Suitable for UNIX Workgroup
- ♦ Support 5V & 3.3V PCI slot.
- ♦ IRQ & I/O mapping automatically assigned by PCI plug & play function.
- **♦** Just use 5V power supply for RS232 & RS422 serial port.
- **◆** Each serial port can set to RS232 or RS422 independently.
- **♦** Support surge protector in TXD/RXD signal line.

P5188U Specification

System Structure:

▲intelligent PCIPORT Card.

▲ external cable with eight standard DB25/DB9 connector.

Serial Communication Controller:

▲type: 16550A compatible with PGA support.

▲speed: 1.8432MHz.

Software Compatibility:

▲DOS Library

▲WIN2003/Vista32

▲WIN2000/XP

▲WIN95/98/Me

▲ Windows NT

▲Linux

▲SCO OpenServer

System I/O & IRQ mapping:

▲one 64byte and one 8byte I/O mapping assigned by PCI BIOS.

▲one IRQ mapping assigned by PCI BIOS.

Port capability:

▲Number of port: 8 ports per card.

▲Interface: RS232 or RS422 selectable

independently.

▲Baud Rate:

each port can be configured to

50~115200bps.

▲Connector type:

DB25 male connector. (with R801 cable) DB9 male connector. (with R804 cable)

Hardware Compatibility:

▲5V & 3.3V PCI bus slot.

Dimension:

▲P5188U card: 6.0 * 4.2 inch.

Environment:

 \triangle operating temperature : 0°C to 55°C.

▲operating humidity: 10% to 95% RH.

 \triangle storage temperature : 0°C to 65°C.

▲storage humidity: 5% to 95% RH.

☆Other relative 5V power supply only eight port card product line:

Model	RS232	RS422	RS485
P5188U	8	8	0
P5288U	8	0	8
P5388U	0	8	8
P5488U	8	4	4
P5588U	8	0	0
P5688U	8	6	2
P5788U	8	7	1
P5888U	4	4	8
P5988U	4	8	4



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net

WEB: http://www.computex.com.tw/rayon

WEB: http://www.rayontech.com