

SEMIL-2000 Series

2U 19"/2 rack mount IP69K waterproof computer supporting Intel® 14th / 13th/ 12th-Gen Core™ processor with M12 10GbE and M12 PoE+ ports

Key Features



CE FC

- IP69K waterproof computer
- -40°C to 70°C wide-temperature fanless operation
- 2x 10GbE, 1x GbE, and 4x 2.5GbE PoE+ via M12 X-coded connectors (SEMIL-2007)
Up to 8x Ethernet ports and 4x PoE+ via M12 X-coded connectors (SEMIL-2008)
- 2x SocketCAN and 2x USB3.2 Gen1 Type-C w/ DP alternative mode
- 8V to 48V wide-range DC input with reverse polarity protection and built-in ignition power control
- MIL-STD-810H compliant

CONTACT US

GET QUOTE

*R.O.C Patent No. I697759
*CN Patent Pending

Introduction

SEMIL-2000 is an extreme-rugged embedded platform with an IP69K-rated dustproof and waterproof design in a 2U 19" rack-mount form factor. Featuring Neosys' advanced thermal design, it ensures fanless operation across -40°C to 70°C wide-temperature ranges and offers dual 5Gbps Type-C ports with DisplayPort signal output.


SEMIL-2000 is powered by Intel's 14th/ 13th/ 12th-Gen platform. The platform benefits from Intel® 7 photolithography, the latest Core™ desktop processors come with a hybrid configuration consisting of performance and efficient cores, and it can support up to 128GB DDR5 memory.

The system adopts a corrosion-proof stainless steel and aluminum chassis to counteract moisture and salinity. Utilizing all M12 connectors to guarantee extreme-rugged connection in shock and vibration environments, it offers a variety of I/O connectivity, two CAN bus 2.0 with SocketCAN driver, two USB 3.2, seven Ethernet (including two 10GbE), and four 802.3at PoE+ ports to supply 25.5W of power per port to connected compatible devices. Internal expansion-wise, it has an M.2 M-key socket to support NVMe SSD and mini-PCIe sockets for extending feature sets. Additionally, SEMIL-2000 features two 2.5" SATA SDD/ HDD accommodation, 8-48V wide-range DC input with ignition power control, and it is in compliance with MIL-STD-810H standards.


Specifications

	SEMIL-2007	SEMIL-2008		SEMIL-2007	SEMIL-2008
System Core			Storage Interface		
Processor	Supporting Intel® 14th-Gen Core™ CPU (LGA1700 socket, 65W/ 35W TDP) - Intel® Core™ i9-14900/ i9-14900T - Intel® Core™ i7-14700/ i7-14700T - Intel® Core™ i5-14500/ i5-14400/ i5-14500T - Intel® Core™ i3-14100/ i3-14100T		SATA HDD	2x Internal SATA port for 2.5" HDD/ SSD installation, supporting RAID 0/ 1	
	Supporting Intel® 13th-Gen Core™ CPU (LGA1700 socket, 65W/ 35W TDP) - Intel® Core™ i9-13900E/ i9-13900TE - Intel® Core™ i7-13700E/ i7-13700TE - Intel® Core™ i5-13500E/ i5-13400E/ i5-13500TE - Intel® Core™ i3-13100E/ i3-13100TE		M.2	1x M.2 2280 M key NVMe socket (PCIe Gen4x4) for NVMe SSD	
	Supporting Intel® 12th-Gen Core™ CPU (LGA1700 socket, 65W/ 35W TDP) - Intel® Core™ i9-12900E/ i9-12900TE - Intel® Core™ i7-12700E/ i7-12700TE - Intel® Core™ i5-12500E/ i5-12500TE - Intel® Core™ i3-12100E/ i3-12100TE - Intel® Pentium® G7400E/ G7400TE - Intel® Celeron® G6900E/ G6900TE		Expansion Bus		
			Mini PCI-E	3x full-size mini PCI Express socket with SIM slot	
Chipset	Intel® Q670E platform controller hub	Intel® R680E platform controller hub	M.2	1x M.2 2242/3052 B key socket with dual SIM slot for M.2 5G/ 4G module 1x M.2 2230 E key socket for Wi-Fi	
				-	
Graphics	Integrated Intel® UHD Graphics 770 (32EU)		Power Supply		
Memory	Up to 128 GB DDR5 4800 SDRAM (two SODIMM slots)	Up to 128 GB ECC/ non-ECC DDR5 4800 SDRAM (two SODIMM slots)	DC Input	8V to 48V DC input, with reverse polarity protection (M12 L-coded)	
AMT	Supports Intel vPro/ AMT 16.0		Ignition Control	Built-in ignition power control (IGN/ GND signal via M12 L-coded connector)	
TPM	Supports dTPM 2.0		Mechanical		
I/O Interface			Dimension	220mm (W) x 310mm (D) x 90.5mm (H)	
Ethernet Port	2x 10GbE Ethernet by X550-AT2 (with WoL) (M12 X-coded) 4x 2.5GbE Ethernet by Intel I226-IT (PoE+) (M12 X-coded) 1x GbE Ethernet by Intel I219-LM (with WoL) (M12 X-coded)		Weight	6 kg	
PoE+	4x IEEE 802.3at PoE+ PSE with 100 W total power budget		Mounting	Rack-mounting (optional) and wall-mounting (standard)	
CAN Bus	2x isolated CAN 2.0 port, supporting SocketCAN in Linux		Environmental		
USB	2x Type-C USB 3.2 Gen1x1 (5Gbps) ports (shared DisplayPort) 2x USB 2.0 ports (M12 A-coded)		Operating Temperature	With 35W CPU -40°C to 70°C	
Video Port	2x Type-C USB connector supporting DP output (shared USB3.2 Gen1x1)			With CPU operating >= 65W CPU -40°C to 70°C (configured as 35W TDP mode) -40°C to 60°C (configured as 65W TDP mode)	
Serial Port	2x isolated 3-wire RS-232 ports (COM1/ COM2)	-	Storage Temperature	-40°C ~85°C	
	1x isolated 3-wire RS232 (COM3) & 1x RS-422/ 485 port (COM4)		Humidity	10%~90% , non-condensing	
			Vibration	MIL-STD-810H: 514.8C-VII. Category 4	
			Shock	MIL-STD-810H: 516.8 Procedure I	
			EMC	EN 50121 (EN 50155 EMC) CE/FCC Class A, according to EN 55032 & EN 55035	
			Ingress Protection	IP69K	

Appearance




SEMIL-2007



SEMIL-2008

Dimensions



Unit : mm

Mounting Configuration



▲ SEMIL 19" rack-mount



▲ SEMIL wall-mount







Ordering Information

Model No.	Product Description
SEMIL-2007	19"/2 rack mount IP69K waterproof computer supporting Intel® 14th/ 13th/ 12th-Gen Core™ processor with 2x M12 10GbE and 4x M12 PoE+ ports
SEMIL-2008	19"/2 rack mount IP69K waterproof computer supporting Intel® 14th / 13th/ 12th-Gen Core™ processor with M12 ports of 2x 10GbE, 1x GbE, 1x 2.5GbE and 4x 2.5GbE PoE+ ports

Optional Accessories

PA-280W-CW6P-2P	280W AC-DC power adapter 24V 11.67A, 85~264VAC, -30~+70°C w/ Wafer FML6P to 2P End Terminal cable for AWP/SEMIL
PA-600W-C4PY-4P	600W AC-DC power adapter 24V 25A, 85~264VAC, -20~+70°C, w/ 4PY Terminal to 4P End Terminal cable for AWP/SEMIL
JPlate-SL	Joint plate for dual SEMIL assembly (for SEMIL-2000)
Rmkit-SL	Rack mount for single SEMIL (for SEMIL-2000)

SEMIL-2000 Series

Type	Model Name	Description
	Cbl-TpCPlug-DPM-1M	TypeC Male Plug to DP Male Cable, Length : 1M
	Cbl-TpCPlug-U3TA-50CM	TypeC Male Plug to USB3.0 Type-A FML, Length: 50CM
	Cbl-TpCPlug-UTpCF-50CM	TypeC Male Plug to USB Type-C FML Cable, Length : 50CM
	Cbl-M12X8M-RJ45-500CM	M12(8-pole-X-coded) to RJ45 Plug, CAT6, Length : 500CM
	Cbl-M12A8M-2U2TA-180CM2	M12 (8-pole-A-coded) to 2xUSB 2.0 type A (female), Length: 180CM
	Cbl-M12A8M-2DB9M_OW2-180CM1	M12 A-Code Male 8P to x2 DB9 Male+2P, Length: 180CM
	Cbl-M12A8M-2DB9M-180CM	M12 (8-pole-A-coded male) to 2x DB9 male, Length: 180CM
	Cbl-M12L5F-CordEnd5-180CM	M12 L-Code 5P(FML) to Cord End Terminal 5P, Length: 1.8M

Cable Kit

SEMIL-2000 M12 cable kit		
Cblkit-M12-SEMIL2007	7x Cbl-M12X8M-RJ45-500CM	1x Cbl-M12A8M-2U2TA-180CM2
	2x Cbl-M12A8M-2DB9M_OW2-180CM1 (COM1/2 & CAN1/2)	1x Cbl-M12A8M-2DB9M-180CM (COM3/4)
	1x Cbl-M12L5F-CordEnd5-180CM	
Cblkit-M12-SEMIL2008	8x Cbl-M12X8M-RJ45-500CM	1x Cbl-M12A8M-2U2TA-180CM2
	1x Cbl-M12A8M-2DB9M_OW2-180CM1 (CAN1/2)	1x Cbl-M12A8M-2DB9M-180CM (COM3/4)
	1x Cbl-M12L5F-CordEnd5-180CM	